

09/744042

CLAIM AMENDMENTS

Claims 1-11 (Cancelled).

1 12. (New) An apparatus for cutting fish and fish fillets into slices comprising;
a cutting unit for cutting the fish/fillets into slices made relative to a horizontal plane;
a feeding unit having means for feeding the fish/fillets to the cutting unit, means for collecting
and processing data on the fish/fillets having means for registering a length of the fish/fillet relative to
a feeding direction and/or a weight of the fish/fillet, the feeding unit having an adjustable plane on
which the fish/fillet is placed and fed forward, means for ^{automatically} ~~automatically~~ adjusting and setting an angle
of the plane, relative to the horizontal plane, responsive to the collecting and data processing
means, continuously during cutting, the angle set as a function of the length and/or the weight of
the fish/fillet for cutting the fish/fillet into a plurality of slices having an equal length for a given
thickness, the apparatus having gripping means for removing each cut slice from the cutting area.

DP
6-10-04

2 13. (New) The apparatus according to claim 12, wherein a sensor unit is placed at a
distance relative to the cutting unit and opposite to the feeding direction for registering a
beginning and an end of each fish/fillet.

3 14. (New) The apparatus of claim 13 wherein the sensor unit is a photocell.

4 15. (New) The apparatus according to claim 12, wherein the gripping means comprise at
least one jaw connected in a pivotal manner around an axis.

5 16. (New) The apparatus according to claim 12, wherein the gripping means comprise at least one jaw part which is displaceable in a linear manner.

6 17. (New) The apparatus according to claim 12, further comprising securing elements for securing the fish/fillet during cutting.

7 18. (New) The apparatus according to claim 16, wherein the securing elements are wheels/drums having a periphery in which barbs are mounted which engage and secure the fish/fillet.

8 19. (New) The apparatus according to claim 12, wherein the automatic angle adjustment means comprise a microprocessor.

9 20. (New) The apparatus according to claim 12, wherein the means for setting the angle of the plane comprise a motor and a spindle to which the plane is mounted.

10 21. (New) A method of cutting fish and fillets into slices made relative to a horizontal plane comprising;

placing a fish/fillet on a feeding unit and conveying the fish/fillet to a cutting area;

feeding the fish/fillet onto an angle adjustable conveyor in the cutting area;


setting the angle adjustable conveyor at a given angle in relation to the horizontal plane, continuously adjusting the angle relative to each slice to provide each slice with a uniform length for a given thickness and continuously adjusting the angle during cutting of an individual slice;

DP
6-10-04

feeding the fish/fillet a given first distance until a sensor is activated;
activating the cutting unit for horizontally cutting the slice;
removing the slice from the cutting area, then, repeating the feeding, adjusting and cutting
steps for each cut made thereafter to provide a plurality of slices of uniform length for a given
thickness.

¹⁰
11 ~~22~~. (New) The method according to claim ~~21~~, further comprising using a gripping device
to remove the slice from the cutting area, using a combined linear and rotating movement of the
gripping device from a start position to an end position.

¹¹
12 ~~23~~. (New) The method according to claim ~~22~~, further comprising, from the end position,
returning the gripping device to the start position while moving the fish/fillet forward the given
first distance.

 13 ~~24~~
¹⁰
²¹
25. (New) The method according to claim ~~20~~, further comprising placing the plurality of
slices into packaging, moving the packaging for a given second distance synchronously while
moving the fish/fillet for the given first distance.

DP
6-10-09